

MMA TRADITIONAL

Manutenzione
Maintenance
Carpenteria leggera
Light carpentry
Cantiere edile
Construction site



- Elettrodi rutili e basici
- Semplici e potenti
- Robuste e durevoli
- Carrozzeria resistente

- Rutile and basic electrodes
- Easy to use and powerful
- Sturdy and durable
- Tough housing

MADE IN SAN MARINO		CE		
		T-ARC 525 LAB	T-ARC 527 LAB	T-ARC 530 LAB
Tensione di rete - Input voltage: 50/60Hz		1 ~ 230/400V		
Potenza assorbita - Absorbed power: 60% / Max		2,5 / 7,5 kW	2,5 / 7,5 kW	5 / 9,5 kW
Fusibile - Fuse		25/20A	32/20A	32/25A
		MMA AC	MMA AC	MMA AC
Campo di regolazione - Welding current		40 - 240A	50 - 240A	26 - 280A 22 - 250A
Selezione uscita - Output selection				50V 70V
Servizio - Duty cycle (40°C EN 60974-1)		220A - 8% 80A - 60%	220A - 10% 90A - 60%	260A - 20% 155A - 60% 230A - 20% 130A - 60%
Tensione a vuoto - Open circuit voltage		44 - 54V	42 - 48V	38 - 77V
Elettrodi : ø mm	Rutile	1,6 - 5,0	1,6 - 5,0	1,6 - 5,0
Electrodes: ø mm	Basico - Basic (AC)	-	-	2,5 - 4,0
Connessioni in uscita - Output connection		DX 25 mmq		DX 50 mmq
Ventilata - Fan cooled		•	•	•
Protezione termostatica - Thermostatic Protection		•	•	•
Peso - Weight ≈		25 kg	28 kg	61 kg
Dimensioni - Dimensions		710 x 350 x 430 mm	420 x 380 x 750 mm	780 x 490 x 615 mm
Codice - Code		205300	219000	205500